






PRODUCT FEATURES

- TUNABLE POWER & CCT
- Includes Slip-Fitter Mount Pre-Attached
- ADC12 Aluminum Heat Sink Housing
- Rotatable Lens for More Applications
- High Performance Optics
- Outdoor Powder Coating
- Bronze Finish
- Photocell Included

- Dimming: 0-10V/PWM/VR
- IP65 Rating Suitable for Wet Locations
- 120 277 Voltage Rating
- 50,000 Hour Lifetime Rating
- DLC Premium Listed
- UL Certified
- 5-Year Limited Warranty
- Operating Temperature: -40°F to 122°F (-40°C to 50°C)

PRODUCT SPECIFICATIONS						
MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN) (L x W x H)	EFFICIENCY (lm/W)
CLF14-150S-UNV-8SC1-T3-SF-BZ-BPC	L150WTUNSLCL14	80 (L) 100 (M) 150 (H)	12,000 15,000 22,500	3000 4000 5000	15.55 x 9.88 x 2.60	150
CLF14-300S-UNV-8SC1-T3-SF-BZ-BPC	L300WTUNSLCL14	200 (L) 240 (M) 300 (H)	30,000 36,000 45,000	3000 4000 5000	18.75 x 12.67 x 2.76	150

DIMMENSIONS



POWER & COLOR ADJUSTABLE CONTROLS

