



LED LINEAR HIGH BAY



PRODUCT FEATURES

- **TUNABLE POWER**
- **TUNABLE CCT: 4000K / 5000K**
- White Finish Frame w/ Iron Housing
- Matte Lens
- Voltage: 120-277V AC
- 0-10V Dimming
- Sensor Ready (JD Item # LENSENSORLHB)
- Includes Chain Mount Accessory
- Pendant Mount Accessory Available (LMOUNTPENDANT11)
- Flicker-free Lighting
- DLC Premium Listed
- UL Certified
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operational Temperature Range -22°F to 122°F (-30°C to 50°C)

PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS L x W x H (in)	EFFICIENCY (lm/W)	CRI
CLHB11-165WBML1-W40/50K	L165WTUNSHBCL11	120 140 165	23,700	4000 5000	24.0 x 14.2 x 1.6	140	> 80
CLHB11-220WBML1-W40/50K	L220WTUNSHBCL11	180 200 220	30,800	4000 5000	24.0 x 14.2 x 1.6	140	> 80
CLHB11-300WBML1-W40/50K	L300WTUNSHBCL11	255 275 300	41,700	4000 5000	24.0 x 14.2 x 1.6	140	> 80

