




LED BYPASS MODE TUBES



PRODUCT FEATURES

- Retrofit / Bypass Mode (Type B)
15W - Double and Single Ended
17W - Double Ended
- Existing Fixture is Wired to Bypass the Ballast
- Non-Dimming
- Low Thermal Decay
- No Mercury, Lead Free
- 100-277 Voltage Rating
- Film Coated Shatter Resistant Glass Tube
- Frosted
- NSF Certified
- UL Classified
- G13 Mounting
- Low Maintenance
- No UV Emission
- IP40 Rating
- 5-Year Limited Warranty
- 50,000 Hour Lifetime Rating
- Operating Temperature Range:
-4°F to 122°F (-20°C to 50°C)

PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	LENGTH (IN)	EFFICIENCY (Lm/W)	BEAM ANGLE
CLT98-15WT8F40K-B ¹	L15T84KBCL98	15	2100	4000	48.0	136	240°
CLT98-15WT8F50K-B ¹	L15T85KBCL98	15	2100	5000	48.0	136	240°
CLT98-17WT8F40K-B ²	L17T84KBCL98	17	2300	4000	48.0	136	240°
CLT98-17WT8F40K-B ²	L17T85KBCL98	17	2300	5000	48.0	136	240°

¹ Double and Single Ended

² Double Ended