

**LED****WALL PACK FIXTURE****30W****80W - 120W****150W****PRODUCT FEATURES**

- Die-Cast Aluminum Alloy Housing
- Bronze Finish
- IP65 Rating - Suitable for Wet Locations
- 120-277 Voltage Rating, PF > 0.9, THD < 20%
- CRI > 80
- Dimmable (80W-150W)
- Tunable Wattage Models Available
- Quick Connect Photocell Integrated on all Models
- Striped Clear Plastic Lens (30W)
- Clear Glass Lens (80W – 150W)
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- DLC Premium Listed
- UL Certified
- Operating Temperature: -40°F to 113°F (-40°C to 45°C)

PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN) (L x W x H)	EFFICIENCY (Lm/W)	TUNABLE WATTAGE
CLW11-305WMBR-S	L30W5KWMTSCL11	30	3,900 - 4,500	3000 4000 5000	5.79 X 8.58 X 3.07	125	NO
CLW11M-805WMBRP	L80W5KWMTCL11	40 50 60 70 80	5,600 7,000 8,400 9,800 11,200	5000	14.37 x 9.33 x 7.36	140	YES
CLW11M-1205WMBRP	L120W5KWMTCL11	80 90 100 110 120	11,200 12,600 14,000 15,400 16,800	5000	14.37 x 9.33 x 7.36	140	YES
CLW11L-1505WMBR	L150W5KWMCL11	150	21,000	5000	17.87 x 9.40 x 8.98	140	NO

