



PRODUCT FEATURES

- HID Replacement for Applications from 50 - 250 Watts
- Suitable for Damp Locations
- IP64 Rating
- 120-277 Voltage Rating, PF > 0.9
- CRI > 80
- Non-Dimming
- Can Be Used in Base Up or Base Down Applications
- Suitable for Total Enclosed Fixture
- UL Certified
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operational Temperature Range: -40°F to 113°F (-40°C to 45°C)

PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN)	BASE	BEAM ANGLE
CLC11-18WBCA1-50K	L18W5KCL11	18	2250	5000	Ø2.36 x 5.71	E26	360°
CLC11-36WBCA1-50K	L36W5KCL11	36	4500	5000	Ø3.35 x 7.91	E26	360°
CLC11-36WBCA1-EX50K	L36W5KMOGCL11	36	4500	5000	Ø3.35 x 8.42	EX39	360°
CLC11-54WBCA1-EX50K	L54W5KMOGCL11	54	6750	5000	Ø3.35 x 9.96	EX39	360°
CLC11-100WBCA1-EX50K	L100W5KMOGCL11	100	12,500	5000	Ø5.12 x 10.43	EX39	360°

