



LED HID RETROFIT

REDUCED ENVELOPE SERIES



PRODUCT FEATURES

- HID Replacement for Applications from 50 - 175 Watts
- High Lumen Output: 155 Lm/W
- CRI > 80
- 1 - 10 V Dimming
- IP64 Rating
- 120-277 Voltage Rating
- Suitable for Total Enclosed Fixture
- Can Be Used in Base Up or Base Down Applications
- 50,000 Hour Lifetime Rating
- DLC Listed
- UL Certified
- 5-Year Limited Warranty
- Operational Temperature Range: -40°F to 113°F (-40°C to 45°C)

PRODUCT SPECIFICATIONS

| MODEL | ITEM # | POWER (W) | LUMENS (LM) | CCT (K) | DIMENSIONS (IN) | BASE | BEAM ANGLE |
|-----------------------|----------------|-----------|-------------|---------|-----------------|------|------------|
| CLC5-18W-RE-50E26 | L18W5KRECLC5 | 18 | 2790 | 5000 | Ø2.36 x 6.42 | E26 | 360° |
| CLC5-36W-RE-50E26 | L36W5KRECLC5 | 36 | 5580 | 5000 | Ø2.36 x 8.27 | E26 | 360° |
| CLC5-100W-REL-50EX39* | L100W5KMOGCLC5 | 100 | 15,500 | 5000 | Ø3.46 x 11.85 | EX39 | 360° |

* DLC Listed

