

**LED****FLOOD FIXTURE****Available Accessories****2-Head Base****Ground Stake****PRODUCT FEATURES**

- Die-Cast Aluminum Alloy Housing
- Bronze Finish
- IP65 Rating- Suitable for Wet Locations
- Tunable Power (13W / 20W / 25W)
- Tunable CCT (3000K/4000K/5000K)
- Knuckle Mount Included
- 0-10V Dimming
- H5V5 Medium Wide Light Distribution/85° Beam Angle
- High Light Transmittance PC Lens
- 120-277 Voltage Rating, PF > 0.9
- 80+ CRI
- UL Certified
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operational Temperature Range -40°F to 113°F (-40°C to 45°C)

PRODUCT SPECIFICATIONS

MODEL	Item #	POWER (W)	CCT (K)	LUMENS (lm)	DIMENSIONS L x W x H (in)	EFFICIENCY (lm/W)	DISTRIBUTION / BEAM ANGLE
CLF11-25WBH5DA1	L25WTUNBULCL11	25	3000	3125	7.28 x 3.66 x 3.74	125 - 140	H5V5 Medium-Wide 85°
			4000	3500			
			5000	3375			

