

LED FLOOD FIXTURE Tunable Wattage & CCT











PRODUCT FEATURES

- TUNABLE POWER (35W/45W/60W)
- TUNABLE CCT (3000K/4000K/5000K)
- ADC12 Aluminum Heat Sink Housing
- Outdoor Powder Coating
- Bronze Finish
- Photocell included (ON/OFF switch)
- 120-277 Voltage Rating, PF > 0.9
- CRI > 80

- Clear Tempered Glass
- 0-10V Dimming Standard
- IP65 Rating Suitable for Wet Locations
- DLC Premium Listed
- UL Certified
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operating Temperature:
 -22°F to 122°F (-30°C to 50°C)

PRODUCT SPECIFICATIONS							
MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN)	EFFICIENCY (lm/W)	BEAM ANGLE
CLF11-60WBH8DA1- BRPAMW30/40/50 (Includes Knuckle Mount)	L60WTUNFLKNCL11	35 45 60	4,900 6,300 8,400	3000 4000 5000	8.66 x 9.84 x 2.28	140	115°x110°
CLF11-60WBH8DA1- BRPFMW30/40/50 (Includes Yoke Mount)	L60WTUNFLYKCL11	35 45 60	4,900 6,300 8,400	3000 4000 5000	9.21 x 7.67 x 2.25	140	115°x110°







