



**PRODUCT FEATURES**

- Die-Cast Aluminum Heat Sink Housing
- UV Stabilized Powder Coated Finish
- IP66 Rating
- 6KV Surge Protection
- DLC Premium Listed
- UL Listed
- High Performance Optics
- Bronze Finish
- 120-277 Voltage Rating
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty

**PRODUCT SPECIFICATIONS**

| MODEL         | POWER (W) | LUMENS (LM) | CCT (K) | DIMENSIONS (IN)<br>(L x W x H) | EFFICIENCY<br>(lm/W) | BEAM ANGLE | MOUNT   |
|---------------|-----------|-------------|---------|--------------------------------|----------------------|------------|---------|
| CLF8-15P5KNBR | 15        | 1475        | 5000    | 5.1 x 1.57 x 4.72              | 122                  | 80° x 120° | KNUCKLE |
| CLF8-30P5KNBR | 30        | 3300        | 5000    | 8.9 x 1.9 x 8.8                | 118                  | 80° x 120° | KNUCKLE |
| CLF8-30P5YKBR | 30        | 3300        | 5000    | 8.9 x 1.9 x 7.2                | 118                  | 80° x 120° | YOKE    |
| CLF8-50P5KNBR | 50        | 5560        | 5000    | 8.9 x 1.9 x 8.8                | 122                  | 80° x 120° | KNUCKLE |
| CLF8-50P5YKBR | 50        | 5560        | 5000    | 8.9 x 1.9 x 7.2                | 122                  | 80° x 120° | YOKE    |

**LINE DRAWING**

