



LED BACKLIT PANEL

Tunable Wattage & CCT



PRODUCT FEATURES

- Seamless White Finish Frame
- Concave-Convex Edge Fold Aluminum Backplate
- Back-lit LED Technology
- No LGP - Non-Yellowing Optical Lens
- DLC Listed
- UL Certified
- Tunable Power & CCT Available
- 0-10V Dimming
- High Luminous Efficiency
- Flicker-free Lighting
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operational Temperature Range
-13°F to 104°F (-25°C to 40°C)

PRODUCT SPECIFICATIONS

MODEL	POWER (W)	VOLTAGE (V)	CCT (K)	DIMENSIONS (mm)	EFFICIENCY (lm/W)	CRI
CLP7-1X4-BLS-40WD-PCDN	25	120-277	3500	298 x 1209 x 30	110	> 80
	30		4000			
	40		5000			
CLP7-2X2-BLS-40WD-PCDN	25	120-277	3500	602 x 602 x 30	110	> 80
	30		4000			
	40		5000			
CLP7-2X4-BLS-50WD-PCDN	30	120-277	3500	602 x 1209 x 30	110	> 80
	40		4000			
	50		5000			

