




# LED DUAL MODE TUBES



## PRODUCT FEATURES

- Direct Replacement / Plug & Play Mode (Type A) \*
- Retrofit / Bypass Mode - Double and Single Ended (Type B)
- Bypass installation utilizes existing lamp holders
- Film Coated Shatter Resistant Glass Tube
- Frosted
- Instant On / No Flicker
- Non-Dimming
- 120-277 Voltage Rating, PF > 0.9
- G13 Mounting
- DLC Listed
- UL Certified
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operating Temperature Range: -4°F to 104°F (-20°C to 40°C)

\* See Ballast Compatibility Chart

## PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	LENGTH (IN)	EFFICIENCY (Lm/W)	BEAM ANGLE
CLT95-18WT8L03-35-AB-Y	L18T835KABCL95	18	2100	3500	48.0	116	180°
CLT95-18WT8L03-40-AB-Y	L18T84KABCL95	18	2100	4000	48.0	116	180°
CLT95-18WT8L03-50-AB-Y	L18T85KABCL95	18	2100	5000	48.0	116	180°

