




LED BYPASS MODE TUBES



PRODUCT FEATURES

- Type B Ballast Bypass - Single and Double Ended
- Film Coated Shatter Resistant Glass Tube
- Frosted
- 120-277 Voltage Rating, PF > 0.9
- CRI > 80
- G13 (Medium Bi-Pin) Mounting
- Dimmable with 0-10V Dimming System*
- DLC Listed
- NSF Certified
- UL Certified
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operating Temperature Range: -4°F to 113°F (-20°C to 45°C)

PRODUCT SPECIFICATIONS

MODEL	POWER (± 10%)	CCT	LUMENS (± 10%)	LENGTH (± 0.05 in.)	EFFICIENCY	BEAM ANGLE	FIELD ANGLE
CLT97-15WB-40K	15W	4000K	1900lm	47.72 in.	126 Lm/W	200°	320°
CLT97-15WB-50K	15W	5000K	1950lm	47.72 in.	130 Lm/W	200°	320°
CLT97-18WB-40K	18W	4000K	2250lm	47.72 in.	125 Lm/W	200°	320°
CLT97-18WB-50K	18W	5000K	2250lm	47.72 in.	125 Lm/W	200°	320°

* Dimming Module + 0-10V/1-10V Dimming Switch.

