



LED UFO HIGH BAY FIXTURE

Tunable Wattage & CCT



PRODUCT FEATURES

- TUNABLE POWER**
 - 100W / 120W / 150W or 180W / 200W / 240W
- TUNABLE CCT - 4000K / 5000K**
- Die-Cast Aluminum Alloy Housing
- Black Finish
- 120-277 Voltage Rating, PF > 0.9, THD < 20%
- CRI > 80
- Mercury and UV Free
- Dimming: 0-10V
- Sensor Ready
- Clear PC Lens
- 1/2" Female Thread for Stem Mount
- IP65 Rating - Suitable for Wet Locations
- 6kV Surge Protection
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- DLC Premium Listed
- UL Certified
- Operating Temperature:
-40°F to 122°F (-40°C to 50°C)

PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	EFFICIENCY (lm/W)	DIMENSIONS (IN) D x H	BEAM ANGLE
CLU11-150WS1BT2A1-BH40/50WD	L150WTUNUFOCL11	100	14,500	4000	154	Ø 10.83 x 5.75	90°
		120	17,400	5000	145		
		150	21,750				
CLU11-240WS1BT2A1-BH40/50WD	L240WTUNUFOCL11	180	26,100	4000	154	Ø 12.60 x 6.80	90°
		200	29,000	5000	145		
		240	34,800				

